

AFE2256 适用于数字 X 射线平板检测器的 256 通道模拟前端

1 特性

- 256 通道
- 片上, 16 位 ADC
- 光电二极管抗短路
- 高性能:
 - 噪声: 750 电子 RMS (1.2pC 输入电荷范围)
 - 低相关噪声
 - 积分非线性: $\pm 2\text{LSB}$, 带内部 16 位 ADC
 - 扫描时间: $< 20\mu\text{s}$ 至 $204.8\mu\text{s}$
- 积分:
 - 六种可选、满标量程输入范围: 0.6pC (最小) 至 9.6pC (最大)
 - 内部定时发生器 (TG)
 - 内置相关双采样器
 - 流水线式“集成和读取”, 用于提高集成期间的吞吐量数据读取
 - 串行低压差分信令 (LVDS) 输出
- 简单电源方案:
 - $\text{AVDD1} = 1.85\text{V}$
 - $\text{AVDD2} = 3.3\text{V}$
- 低功耗
- 小睡模式和完全断电模式
- 定制 Chip-On-Film (COF) 封装

2 应用

- X 射线平板探测器
- 电荷探测器
- 电容测量

3 说明

AFE2256 是一款 256 通道模拟前端 (AFE), 旨在满足基于平板检测器 (FPD) 的数字 X 射线系统的要求。该器件包含 256 个集成器、1 个用于满量程电荷电平选择的可编程增益放大器 (PGA)、1 个带有双电源的相关双采样器和 256:4 模拟多路复用器。

该器件还具有四个 16 位逐次逼近寄存器 (SAR) 模数转换器 (ADC)。来自 ADC 的串行数据采用低压差分信令 (LVDS) 格式。

小睡和断电模式能够大幅降低功耗, 在由电池供电的系统中极其实用。


申请完整数据表或其他设计资源: [申请 AFE2256](#)

封装信息

器件型号	封装 ⁽¹⁾	封装尺寸 ⁽²⁾
AFE2256	TDU (COF, 320)	38.00mm x 28.00mm
	TDR (COF, 325)	48.35 mm x 21.5 mm
	TBN (COF, 325)	48.35 mm x 21.5 mm

(1) 有关所有可用封装, 请参阅节 6。

(2) 封装尺寸 (长 × 宽) 为标称值, 并包括引脚 (如适用)。



AFE2256 方框图



Table of Contents

1 特性.....	1	4.2 Trademarks.....	3
2 应用.....	1	4.3 静电放电警告.....	3
3 说明.....	1	4.4 术语表.....	3
4 Device and Documentation Support.....	3	5 Revision History.....	3
4.1 Documentation Support.....	3	6 Mechanical, Packaging, and Orderable Information....	3

4 Device and Documentation Support

4.1 Documentation Support

4.1.1 Related Documentation

For related documentation, see the following:

Texas Instruments, [TPS7A8300 2- \$\mu\$ A, 6- \$\mu\$ VRMS, RF, LDO Voltage Regulator data sheet](#)

4.2 Trademarks

所有商标均为其各自所有者的财产。

4.3 静电放电警告



静电放电 (ESD) 会损坏这个集成电路。德州仪器 (TI) 建议通过适当的预防措施处理所有集成电路。如果不遵守正确的处理和安装程序，可能会损坏集成电路。

ESD 的损坏小至导致微小的性能降级，大至整个器件故障。精密的集成电路可能更容易受到损坏，这是因为非常细微的参数更改都可能会导致器件与其发布的规格不相符。

4.4 术语表

[TI 术语表](#) 本术语表列出并解释了术语、首字母缩略词和定义。

5 Revision History

注：以前版本的页码可能与当前版本的页码不同

Changes from Revision B (May 2016) to Revision C (December 2023)	Page
• 通篇添加了 AFE2256TBN 封装规格.....	1
• 为了清晰起见，更改了首页原理图.....	1
Changes from Revision A (July 2015) to Revision B (May 2016)	Page
• 添加了申请完整数据表的链接.....	1
Changes from Revision * (March 2015) to Revision A (July 2015)	Page
• 发布为量产.....	1

6 Mechanical, Packaging, and Orderable Information

The following pages include mechanical, packaging, and orderable information. This information is the most current data available for the designated devices. This data is subject to change without notice and revision of this document. For browser-based versions of this data sheet, refer to the left-hand navigation.

PACKAGING INFORMATION

Orderable part number	Status (1)	Material type (2)	Package Pins	Package qty Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
AFE2256TBN	Active	Production	COF (TBN) 325	32 JEDEC TRAY (5+1)	Yes	AU	N/A for Pkg Type	0 to 70	AFE2256TBN
AFE2256TBN.A	Active	Production	COF (TBN) 325	32 JEDEC TRAY (5+1)	Yes	AU	N/A for Pkg Type	0 to 70	AFE2256TBN
AFE2256TDR	Active	Production	COF (TDR) 325	32 JEDEC TRAY (5+1)	Yes	AU	Level-1-260C-UNLIM	0 to 85	AFE2256TDR
AFE2256TDR.A	Active	Production	COF (TDR) 325	32 JEDEC TRAY (5+1)	Yes	AU	Level-1-260C-UNLIM	0 to 85	AFE2256TDR
AFE2256TDU	Active	Production	COF (TDU) 320	35 EIAJ TRAY (10+1)	Yes	AU	Level-1-260C-UNLIM	0 to 85	AFE2256TDU
AFE2256TDU.A	Active	Production	COF (TDU) 320	35 EIAJ TRAY (10+1)	Yes	AU	Level-1-260C-UNLIM	0 to 85	AFE2256TDU

⁽¹⁾ **Status:** For more details on status, see our [product life cycle](#).

⁽²⁾ **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.

⁽³⁾ **RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.

⁽⁴⁾ **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

⁽⁵⁾ **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.

⁽⁶⁾ **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

Important Information and Disclaimer:The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative

and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

重要通知和免责声明

TI“按原样”提供技术和可靠性数据（包括数据表）、设计资源（包括参考设计）、应用或其他设计建议、网络工具、安全信息和其他资源，不保证没有瑕疵且不做任何明示或暗示的担保，包括但不限于对适销性、与某特定用途的适用性或不侵犯任何第三方知识产权的暗示担保。

这些资源可供使用 TI 产品进行设计的熟练开发人员使用。您将自行承担以下全部责任：(1) 针对您的应用选择合适的 TI 产品，(2) 设计、验证并测试您的应用，(3) 确保您的应用满足相应标准以及任何其他安全、安保法规或其他要求。

这些资源如有变更，恕不另行通知。TI 授权您仅可将这些资源用于研发本资源所述的 TI 产品的相关应用。严禁以其他方式对这些资源进行复制或展示。您无权使用任何其他 TI 知识产权或任何第三方知识产权。对于因您对这些资源的使用而对 TI 及其代表造成的任何索赔、损害、成本、损失和债务，您将全额赔偿，TI 对此概不负责。

TI 提供的产品受 [TI 销售条款](#)、[TI 通用质量指南](#) 或 [ti.com](#) 上其他适用条款或 TI 产品随附的其他适用条款的约束。TI 提供这些资源并不会扩展或以其他方式更改 TI 针对 TI 产品发布的适用的担保或担保免责声明。除非德州仪器 (TI) 明确将某产品指定为定制产品或客户特定产品，否则其产品均为按确定价格收入目录的标准通用器件。

TI 反对并拒绝您可能提出的任何其他或不同的条款。

版权所有 © 2026，德州仪器 (TI) 公司

最后更新日期：2025 年 10 月