

## TDA54x Jacinto™ Processors

### 1 Features

#### Processor cores:

- Up-to Eight Arm® Cortex®-A720AE MPUs
  - Lockstep capable

#### Real-Time processing CPUs :

- Up-to 6x Arm® Cortex®-R52+ (or 3x pairs in Lockstep)
  - Virtualization for multi-core processing

#### System/SOC CPUs:

- 8x Dual Arm® Cortex®-M55 (Lockstep)

#### DSP / AI processing :

- Up to 4x C7™ neural processing unit(NPU)
  - Up to 400 TOPS

#### Vision and video processing:

- Up to 16 cameras
- DMPAC: Dense Optical Flow, Stereo Disparity Engine
- 4x CSI-2 RX interface, 1x CSI-2 TX output

#### GPU and display processing:

- Imagination DXS Family GPU

#### Display subsystem:

- eDP1.5/DP2.1
  - Multi-Stream Transport (up to 4 displays, up to 4K60fps)
- 1x DSI CPHY-2.0/DPHY-2.1
  - Up to 4 lanes per port (muxed with CSI-TX)
- DSS Controller:
  - 4 pipelines + 1 Writeback path, up to 4k60 per pipe

#### Networking subsystem:

- NPAC (Network Processing Accelerator) specialized subsystem for Ethernet switching and packet transfer
- Integrated Ethernet Switch
  - 8 external ports
  - 10base-T1S (OA3P 3-wire i/f) supported on all ports
  - MACSEC per port, supports line rate

#### Memory:

- LPDDR4x/5/5x interface
  - In-line ECC
- 1x UFS3.0

- 1x eMMC5.1 HS200
- 2x XSPI interface up to 400MBps

#### Security:

- SHE/EVITA Full compliant HSM, ISO21434 compliant

#### Functional Safety:

- [Functional Safety-Compliant](#) targeted for ISO26262 and IEC61530
- AEC - Q100 qualified

#### Safety features:

- Support for full ASIL D or mixed ASIL D / ASIL B with FFI

#### High-speed serial interfaces:

- 2x PCIe up to 4L
  - Gen5 controller
  - Root complex or Endpoint
- 1x USB3.2 (Gen 2)/eUSB2.0

#### Video acceleration:

- H.264/H.265 Encode/Decode: 1.0GP/s encode or decode, up to 10b support

#### Serial interfaces:

- Up to 170 General-Purpose Input/Output (GPIO) pin capability

#### TPS6594-Q1 Companion Power Management ICs (PMIC):

- Functional Safety-Compliant support up to ASIL D/SIL 3
- Flexible mapping to support different use cases



## 2 Applications

- **Automotive:**
  - Autonomous sensor fusion / perception systems including camera, radar and LiDAR sensors
  - ADAS Domain Controller
  - Advanced surround view and park assistance systems
  - Off-highway vehicle control
- **Industrial:**
  - Industrial mobile robot (AGV/AMR) with safety functions
  - Construction and agriculture
  - Aerospace and defense

## 3 Description

The TDA5 high-performance compute SoC family is designed to deliver safe and efficient edge AI performance, with capabilities of up to 1200 TOPS, with integrated C7™ NPU and chiplet-ready architecture. This enables seamless progression to L3 autonomous driving in software-defined vehicles, where conditional automation is possible in both urban and highway environments. Additionally, the TDA5 SoCs are well-suited for similar applications in industrial transportation, humanoid and industrial robots, and aerospace and defense with their advanced sensor processing, cybersecurity, and functional safety features.

The TDA5 SoCs feature multiple specialized subsystems, each tailored to address the growing demand for high-performance compute and cross-domain applications. These subsystems include dedicated processing cores and hardware acceleration for security, vision processing, edge AI, display rendering, and networking. By offloading these tasks, the SoCs' MPU and MCU cores are freed up to focus on user application software. Furthermore, support for PCIe, Ethernet, and other automotive standard peripherals enables safe, secure, and high-speed data transfer between different components and systems.

Building on two decades of leadership in the automotive processor market, the TDA5 architecture is designed to provide a scalable and high-performance solution for a wide range of applications. As an evolution of the TDA4 family, software developed for TDA4 can be easily scaled to the TDA5 family, with minimal rework required. This allows for the reuse of software assets and enables the development of more complex and sophisticated applications. The TDA5 family's unique combination of high-performance real-time and analytics cores, along with the latest C7™ NPU and next-generation accelerators for image signal processing, makes it an optimized solution for various camera, radar, sensor fusion, and AI applications.

The TDA5 family provides high-performance compute capabilities for both traditional computer vision and deep learning algorithms, with industry-leading power/performance ratios. The high level of system integration enables lower costs for advanced automotive platforms, supporting multiple sensor modalities in centralized ECUs, multiple sensor domains, or a centralized automotive computer. Key processing and acceleration cores include the latest-generation C7™ DSP with scalar and vector cores, dedicated deep learning acceleration, latest application and GPU cores for general compute, a vision and imaging subsystem, video codec, network packet processing accelerator, and Ethernet switch, as well as a dedicated security subsystem. These cores are carefully integrated into an SoC architecture designed from the ground up to support functional safety at a system level, ensuring the highest level of reliability and performance in safety-critical applications.



PACKAGING INFORMATION

Orderable part number	Status (1)	Material type (2)	Package   Pins	Package qty   Carrier	RoHS (3)	Lead finish/ Ball material (4)	MSL rating/ Peak reflow (5)	Op temp (°C)	Part marking (6)
XTDA548T5AAPY	Preview	Preproduction	FCBGA (ALF)   827	180   JEDEC TRAY (5+1)	-	Call TI	Call TI	-	

- (1) **Status:** For more details on status, see our [product life cycle](#).
- (2) **Material type:** When designated, preproduction parts are prototypes/experimental devices, and are not yet approved or released for full production. Testing and final process, including without limitation quality assurance, reliability performance testing, and/or process qualification, may not yet be complete, and this item is subject to further changes or possible discontinuation. If available for ordering, purchases will be subject to an additional waiver at checkout, and are intended for early internal evaluation purposes only. These items are sold without warranties of any kind.
- (3) **RoHS values:** Yes, No, RoHS Exempt. See the [TI RoHS Statement](#) for additional information and value definition.
- (4) **Lead finish/Ball material:** Parts may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.
- (5) **MSL rating/Peak reflow:** The moisture sensitivity level ratings and peak solder (reflow) temperatures. In the event that a part has multiple moisture sensitivity ratings, only the lowest level per JEDEC standards is shown. Refer to the shipping label for the actual reflow temperature that will be used to mount the part to the printed circuit board.
- (6) **Part marking:** There may be an additional marking, which relates to the logo, the lot trace code information, or the environmental category of the part.

Multiple part markings will be inside parentheses. Only one part marking contained in parentheses and separated by a "~" will appear on a part. If a line is indented then it is a continuation of the previous line and the two combined represent the entire part marking for that device.

**Important Information and Disclaimer:**The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you fully indemnify TI and its representatives against any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#), [TI's General Quality Guidelines](#), or other applicable terms available either on [ti.com](https://www.ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products. Unless TI explicitly designates a product as custom or customer-specified, TI products are standard, catalog, general purpose devices.

TI objects to and rejects any additional or different terms you may propose.

Copyright © 2025, Texas Instruments Incorporated

Last updated 10/2025